



emergency overflow



Capacity	
Organic daily load	0,48 kg BOD ₅
Hydraulic daily load	1,2 m ³
Water Levels	
H _{BB,min}	1130 mm
H _{BB,max}	1370 mm
HW _{ges}	1480 mm
H _P	480 mm
H _S	1000 mm
Dimension	
Length L	2280 mm
Width B	1985 mm
Height H	2430 mm
Inflow E	205/515 mm
Outflow A	520 mm



Maxi (as option)



<p>D</p> <p>Klaro E Professional 8 EW TD-Mini +P Carat 4800 L / 1268 gal.</p>			<p>Artikel-Nr. product no. article no. artículo no.</p>
<p>GB Klaro E Professional 8 inh. TD-Mini +P Carat 4800 L / 1268 gal.</p>	<p>ES Klaro E Professional 8 PE Cúpula Mini +P Carat 4800 L / 1268 gal.</p>	<p>FR Klaro E Professional 8 EH mini-dôme +P Carat 4800 L / 1268 gal.</p>	<p>revision</p>
<p>gezeichnet drawn</p> <p>ISC</p>	<p>Gewicht weight</p> <p>220 kg</p>	<p>Otto Graf GmbH Carl-Zeiss-Str. 2-6 DE-79331 Teningen mail@graf.info www.graf.info</p>	
<p>Datum date</p> <p>2016.08.15</p>	<p>Toleranz tolerance</p> <p>+/- 3%</p>		
<p>Maßstab scale</p> <p>unmaßst.</p>	<p>Einheiten units</p> <p>mm [inch] gal. = US gal.</p>		